Test Report

Skywalk Cumeo 2 115 | 0923-44442

Equipment	Skywalk Cumeo 2 115 | 0923-44442 Production Date: August 2023
Service	Passed
Rating	Used, very good conditions
Comment	EP004T
Date	17. February 2026
Next Service	February 2028 or after 100 flight hours
Service Center	Eagles Service di Di Ciano Lavinia | Checker: Lavinia Di Ciano

Service Steps	Porosity Test
	Fabric Tear Resistance
	Visual Inspection: Canopy
	Visual Inspection: Lines
	Visual Inspection: Risers
	Linen Tear Strength
	Trimm

Notice

Your glider has undergone a service. Before flying, it is essential that you test-inflate and thoroughly check it.

This service was performed using the WingSolution check software.
Scan the QR code or follow the link below to view the full online version of your service protocol, which includes additional details and a range of extra features.

https://www.wing-solution.com/en/paraglider-services/protocol/4d61bd89-a25c-45ea-accd-4fc8d3c49bdc

Porosity Test

Gauge	HELLO
1. Measurement	> 250 [s]
Rating	**Passed**

Fabric Tear Resistance

Bettsometertest	**Passed**

Visual Inspection: Canopy

Rods	Passed
Loops	Passed
Topsail	Passed
Cell walls	Passed
Lower sail	Passed
Leading edge	Passed
Rating	**Passed**

Visual Inspection: Lines

Main lines	Passed
Brake lines	Passed
Gallery lines	Passed
Rating	**Passed**

Visual Inspection: Risers

Risers	Passed
Line locks	Passed
Speed system	Passed
Rating	**Passed**

Linen Tear Strength

Left / A1	Minimum strength: **50 daN** / Measured strength: **88 daN** - Passed
Rating	**Passed**

Trimm

For additional details and a comprehensive graphic, please refer to the online protocol.

Mainlines

ST	3	2	1		1	2	3	ST
SL	SL	SL → DL	SL → DL	A	SL → DL	SL → DL	SL	SL
	SL	SL	SL	B	SL	SL	SL	
	SL	SL	SL → DL	C	SL → DL	SL	SL	

The left brake line was shortend by 0mm.

The right brake line was shortend by 0mm.

Linen Length: Left

A Linen

Ref.	Act.	Diff.
7950	7952	2
7908	7912	4
7883	7886	3
7907	7912	5
7911	7912	1
7831	7831	0
7847	7848	1
7784	7782	-2
7795	7794	-1
7687	7688	1
7600	7602	2
7596	7596	0
7510	7516	6
7452	7457	5
7474	7474	0
Average		2
Tolerance		(-10,10)

ST Linen

Ref.	Act.	Diff.
7152	7151	-1
7120	7119	-1
7149	7149	0
7058	7060	2
7032	7032	0
7085	7086	1
7155	7157	2
Average		0
Tolerance		(-15,10)

B Linen

Ref.	Act.	Diff.
7877	7880	3
7833	7838	5
7805	7811	6
7831	7838	7
7831	7835	4
7753	7758	5
7770	7775	5
7716	7718	2
7731	7737	6
7613	7617	4
7529	7528	-1
7525	7530	5
7428	7429	1
7377	7382	5
7396	7390	-6
Average		3
Tolerance		(-10,10)

C Linen

Ref.	Act.	Diff.
7981	7982	1
7933	7936	3
7916	7919	3
7900	7901	1
8000	8001	1
7962	7970	8
7859	7867	8
7863	7871	8
7810	7820	10
7827	7838	11
7702	7708	6
7607	7610	3
7594	7595	1
7467	7470	3
7406	7407	1
7414	7424	10
Average		5
Tolerance		(-10,10)

D Linen

Ref.	Act.	Diff.
8041	8045	4
8001	8007	6
7976	7981	5
7962	7965	3
8050	8055	5
7996	8003	7
7903	7910	7
7907	7913	6
7851	7860	9
7867	7876	9
Average		6
Tolerance		(-10,10)

BR Linen

Ref.	Act.	Diff.
8280	8291	11
7995	8009	14
7838	7845	7
7790	7804	14
7715	7720	5
7548	7559	11
7498	7503	5
7526	7540	14
7405	7417	12
7258	7274	16
7185	7193	8
7132	7139	7
Average		10
Tolerance		(-10,50)

Linen Length: Right

A Linen

Ref.	Act.	Diff.
7950	7950	0
7908	7909	1
7883	7889	6
7907	7910	3
7911	7912	1
7831	7831	0
7847	7852	5
7784	7783	-1
7795	7791	-4
7687	7686	-1
7600	7599	-1
7596	7595	-1
7510	7512	2
7452	7453	1
7474	7473	-1
Average		1
Tolerance		(-10,10)

ST Linen

Ref.	Act.	Diff.
7152	7151	-1
7120	7120	0
7149	7150	1
7058	7059	1
7032	7031	-1
7085	7084	-1
7155	7156	1
Average		0
Tolerance		(-15,10)

B Linen

Ref.	Act.	Diff.
7877	7878	1
7833	7836	3
7805	7809	4
7831	7836	5
7831	7838	7
7753	7755	2
7770	7772	2
7716	7716	0
7731	7736	5
7613	7613	0
7529	7530	1
7525	7527	2
7428	7427	-1
7377	7380	3
7396	7391	-5
Average		2
Tolerance		(-10,10)

C Linen

Ref.	Act.	Diff.
7981	7983	2
7933	7934	1
7916	7916	0
7900	7901	1
8000	8001	1
7962	7967	5
7859	7864	5
7863	7868	5
7810	7817	7
7827	7839	12
7702	7707	5
7607	7612	5
7594	7600	6
7467	7465	-2
7406	7406	0
7414	7411	-3
Average		3
Tolerance		(-10,10)

D Linen

Ref.	Act.	Diff.
8041	8046	5
8001	8006	5
7976	7980	4
7962	7966	4
8050	8055	5
7996	7999	3
7903	7908	5
7907	7911	4
7851	7856	5
7867	7875	8
Average		5
Tolerance		(-10,10)

BR Linen

Ref.	Act.	Diff.
8280	8287	7
7995	8003	8
7838	7851	13
7790	7803	13
7715	7721	6
7548	7560	12
7498	7503	5
7526	7535	9
7405	7417	12
7258	7274	16
7185	7197	12
7132	7149	17
Average		11
Tolerance		(-10,50)